

Silverton 34c
Bimini Enclosure



Begin installing 9'3" track on the front center of the bridge. Mount the track on top of the feature as shown in this picture. Install a flex rail screw every 4".



Work out from the center toward the corner. Install the screws more often to make the track bend smoothly.

Silverton 34c
Bimini Enclosure



Secure the track to the end following the feature in the bridge as shown in this picture. Repeat on the opposite side.



The 3'9" track starts at the point in this picture. Work down the side of the bridge keeping the track near the inside edge.

Silverton 34c
Bimini Enclosure



On boats without an arch the track can fade to the outside edge. Boats with the arch the track has to stay on the inside edge. Install the 1'3" track from the stanchion back fading to the outside.



Zip all 8 panels to the bimini top and to each other. The rope zipper supplied with the enclosure is for the front 3 panels and the front of each side panel.

Silverton 34c
Bimini Enclosure



Slide the rope zipper into the track around the front of the bridge. Make sure the Velcro on the zipper is facing out. Zip the side curtains to the rope first; this will position the front 3 curtains correctly. Connect the front to each zipper. Partially unzip the tops of the curtain to make it easier to get the bottoms zipped.



Line the cut out in the curtain up with the light; pull tight and mark one button. Install a LTD stud provided and snap the curtain in place. Work out from the center to the zippers. Move to the corner of the bridge. Install a LTD stud in each corner just before the bridge curves around to the side. Pull the curtain tight down and across; mark a button and install. Mark the remaining buttons and install.

Silverton 34c
Bimini Enclosure



There is a LTD at the end of the zipper rope on each side. Install these buttons and the enclosure is complete.