

38 SB SILVERTON
FRAME
PACKING LIST

<u>FRAME:</u>	<u>P/N</u>
<u>5-bow stainless steel frame</u>	<u>1014690FR</u>
<u>6 deck mounts</u>	<u>SSF320</u>
<u>2 angle mounts with quick pins</u>	<u>SSF322-1</u>
<u>2 Split Rail fittings 1"</u>	<u>SSF366</u>
<u>16 #10 x 3/4" oval head screws</u>	<u>OP10075</u>



38 SB Silverton

Frame

Instructions

1. The five bow frame consists of a 2 bow front and 3 bow aft sections.



2. Begin installing mounts for the front section by measuring 3in from the door to center of mount. Secure a deck mount with #10 screws provided. Repeat on opposite side.



3. Secure an angle deck mount in front of cup holder as shown in this picture with #10 screw provided. Repeat on opposite side. Place 2 bow frame in mounts with struts forward.



38 SB Silverton

4. Measure back 13in from door opening and make a reference mark towards the outside edge.



5. Arrange the mount so that it runs parallel with the center line of the boat. Secure with #10 screws provided. Repeat on opposite side.



38 SB Silverton

6. Secure a deck mount inside the aft rail for the middle strut as shown in this picture.



7. Secure the mount in the corner of the feature with #10 screws provided. Repeat on opposite side.



38 SB Silverton

9. Place a split rail fitting on top rail 40in off center with screws facing inboard. Repeat on opposite side.

Place 3 bow frame in mounts with struts aft.